

## SnapXit C40C Compact

### Appearance and Composition

Part Number: C40C  
 Strike Plate: Red anodised aluminium.  
 Base Plate: Black anodised aluminium.  
 Separator: Closed end coil spring  
 Safety Seal: Break-away, replaceable, polypropylene.  
 Impact Tip: Tungsten Carbide  
 Size: 40mm Ø x 8.5mm  
 Weight: 46g  
 Adhesive: 3M VHB 4936 Conformable Foam Tape

### Production Certification

ISO9001:2015

RoHS 2011/65/EU  
 IEC 62321:2008  
 EN 14672:2004  
 EPA 3540C:1996

RoHS 2011/65/EU  
 REACH 2015/863/EU

### Sectors and Usage

Compact C40C devices are used most often in buses, light rail, taxi's, and converted minibuses. They are also used on toughened glass fire extinguisher and first aid kit covers where a lower profile is required.



### Performance Data

Force / Energy	6mm BS 857 Toughened Glass		
N / J	Max strikes to break	Min strikes to break	Average (%)
80 / 1.68	2	1	80% (of 10)
90 / 2.04	2	1	90% (of 10)
100 / 2.39	1	1	100% (of 10)

Results may vary due to the relative toughness and hardness in tempered glass, please be sure the glass is fit for purpose and verified for use with these devices.

**NB. USE ONLY ON CLEARLY MARKED PROPERLY TOUGHENED GLASS**